



azul tortuga

## PRODUCT

Installation	Float, Glue Down
Wear Layer	20mil with Quantum X™ Technology
Core	4mm
Underlayment	1 mm IXPE (No VOC)

## SIZE/PACKAGING

Plank Sizes	7" x 48"
Planks/Carton	10
SF/Carton	24.028
Cartons/Pallet	55
SF/Pallet	1321.54

## DATA

Residential	ENISO10874	Class23
Commercial	ENISO10874	Class33
Peel Strength	EN431   GB/T34440	Pass
Shearing Strength	EN432	Pass
Dimensional Change Upon Heating*	EN434   GB/T34440	0.20%
Warpage	EN434	0.14mm
Scratching	ASTME413	54
Wear Resistance	EN660	2.0mm <sup>3</sup>
Color Fastness	EN20105 + GB/T34440	Pass
Fire Resistance	ASTME84   GB8624	B (1 B-sl)
Slip Resistance	DIN51130	R <sub>9</sub>
Castor Chair Suitability	EN425	Suitable
Chemical Resistance	EN423   ASTM F925	Class 0
Thermal Conductivity (25 °C)	GB/T 10295	0.142W/(m.k)

\*A 50'x50' install requires 10mm expansion space along walls in uncontrolled environments (Such as no HVAC).

